

Effizienz bei niedriger Last 10%		Efficiency at low load (10%)	
C port DC5.0V 3.0A 15.0W	80.7 %	C port DC5.0V 3.0A 15.0W	80.7 %
C port DC9.0V 2.3A 20.7W	80.3 %	C port DC9.0V 2.3A 20.7W	80.3 %
C port DC15.0V 1.4A 21.0W	77.0 %	C port DC15.0V 1.4A 21.0W	77.0 %
C port DC20.0V 1.1A 22W	73.5 %	C port DC20.0V 1.1A 22W	73.5 %
Q port DC5.0V 3.0A 15.0W	80.8 %	Q port DC5.0V 3.0A 15.0W	80.8 %
Q port DC9.0V 2.0A 18.0W	83.6 %	Q port DC9.0V 2.0A 18.0W	83.6 %
Q port DC12.0V 1.5A 18.0W	82.8 %	Q port DC12.0V 1.5A 18.0W	82.8 %
C port + Q port DC5.0V 3.5A 17.5W	82.8 %	C port + Q port DC5.0V 3.5A 17.5W	82.8 %
Leistungsaufnahme bei Nulllast		No-load power consumption	
0.09 W		0.09 W	
Ladestandard		Charging standards	
Power Delivery		Power Delivery	
USB 3.1 PD		USB 3.1 PD	

Weitere Produkteigenschaften

Plattform	Standard (kHE)
Material	
Gehäuse:	
Aluminium, lackiert weiß ähnlich RAL9010	
Abdeckung:	
PA6 GF30 850°C, weiß ähnlich RAL9010	
Lieferumfang	
1x DESK 2 Steckdosenleiste	
inkl. Haltewinkel	
Im Karton	

Further product attributes

Plattform	Standard (kHE)
Material	
Housing:	
Aluminium, painted white similar to RAL 9010	
Cover:	
PA6 GF30 850°C, white similar to RAL 9010	
Scope of delivery	
1x DESK 2 power strip	
incl. Mounting brackets	
In carton	

Umgebungsbedingungen

Maximale Höhe	0 - 2000m
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.	
Umgebungstemperatur bei Transport und Lagerung	-20°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	10 – 90%
Schutzart	IP20

Environmental conditions

Maximum height	0 - 2000m
Surrounding temperature during mounting and use	5°C – 35°C
Protect from direct sunlight.	
Surrounding temperature during transport and storage	-20°C - 60°C
Relative humidity (non-condensing)	10 – 90%
Protection type	IP20

Konformität

Angewandte Normen	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---

Conformity

Applied standards	IEC 62368-1 (USB-Charger) EN 62368-1 (USB-Charger)
--------------------------	---