



NOTES :

1. MATERIAL

- 1.1 HDMI CABLE : ( 30AWG BC\*1P+ 30AWG BC+AM)\*5PCS+ 30AWG BC\*4C+AM+ 28AWG BC+128/0.12ALM+BLACK PVC JACKET.  
OD:  $\varnothing 6.0 \pm 0.2$  mm
- CABLE MARKING:HIGH SPEED HDMI® CABLE WITH ETHERNET
- 1.2 HDMI TYPE A MALE:BLACK INSULATION, GOLD PLATED CONTACTS , GOLD PLATED SHELL .
- 1.3 ALL HOOD:MOLDED BLACK PVC.
2. ELECTRICAL
  - 2.1 100% OPEN AND SHORT TEST.
  - 2.2 CONDUCTOR RESISTANCE: 5 OHMS MAX.
  - 2.3 INSULATION RESISTANCE: 10 MEGOHMS MIN.
  - 2.4 HDTV-DVD TEST:1080P.
3. ALL MATERIALS ARE REACH COMPLIANT.

P/N CHART

CUSTOMER NO	L (MM)
21. 15. 3200	1000 ± 30MM
21. 15. 3201	1800 ± 50MM
21. 15. 3202	3000 ± 70MM
21. 15. 3203	5000 ± 70MM

PIN OUT

P1	P2	
1	1	BLUE
3	3	WHITE
5	5	DRAIN
7	7	BLUE
9	9	WHITE
11	11	DRAIN
13	13	GREEN
14	14	BLUE
17	19	WHITE
19	17	DRAIN
15	15	WHITE
16	16	BLUE
18	18	RED
		SHELL DRAIN SHELL

1-3: RED AM  
 4-6: SILVER AM  
 7-9: BLUE AM  
 10-12: BROWN AM  
 13-15: GREEN AM

**SECOMP**

LENGTH TOLERANCE: X, ± 0.5 .X ± 0.2 .XX ± 0.1	SCALE: FREE	PRODUCT NO:		CUSTOMER NO:		ENG:
ANGLE TOLERANCE: X° ± 3° .X° ± 1°	UNIT: mm	DRAWING NO:		PRODUCT DESCRIPTION:		CHECKED:
	VERSION: 00	PAGE: 1/1		HDMI AM/AM/GOLD-PLATED		APPROVED:
						William
						Jake
						Jason