NOTES:

1. MATERIAL
   1.1 HDMI CABLE:(24AWG BC*1P+ 28AWG BC+AM)*4PCS+(28AWG BC*1P+ 28AWG BC+AM)+28AWG BC *4C+AM+ 28AWG BC+128/0.12ALM+BLACK PVC JACKET.
   OD: ⌀ 9.8 ± 0.2 mm
   CABLE MARKING:HIGH SPEED HDMI® CABLE WITH ETHERNET
   1.2 HDMI 19PIN TYPE A MALE:BLACK INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL .
   1.3 ALL HOOD:MOLDED BLACK PVC.
2. ELECTRICAL
   2.1 100% OPEN AND SHORT TEST.
   2.2 CONDUCTOR RESISTANCE: 10 OHMS MAX.
   2.3 INSULATION RESISTANCE: 5 MEGOHMS MIN.
   2.4 HDTV-DVD TEST : 1080P
3. PACKAGING: 1 PC/POLYBAG+CUSTOMIZED LABEL
4. ALL MATERIALS ARE ROHS AND REACH COMPLIANT.

PIN OUT

| | | | | | |
|---|---|---|---|---|---|
| LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1 | SCALE: FREE | | SECOMP | | ENG: Ann |
| ANGLE TOLERANCE: X° ±3° .X° ±1° | UNIT: mm | | PRODUCT NO: P/N | CUSTOMER NO: 21.15.3205 | CHECKED: William |
| | VERSION: 00 | PAGE: 1/1 | DRAWING NO: | PRODUCT DESCRIPTION: HDMI AM/AM/NICKEL-PLATED,BLACK | APPROVED: |