



MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION
①	CABLE	UTP [24AWG 7*0.19±0.015mm((Bare Copper)*1PR)]*4+PVC OD:5.8±0.3mm COLOR:WHITE
②	RJ45 CONNECTOR	RJ45,8P8C,TWO FORK GOLD PLATED CONTACTS
③	MOLDING	MOLDING PVC , COLOR:WHITE

(1)Jacket Color:White(RAL 9003)

(2)wiring:T568B

Item No.	Length	Tolerance
21.99.1470	0.5	+20/-10
21.99.1471	1	+/-20
21.99.1472	2	+/-40
21.99.1473	3	+/-60
21.99.1475	5	+/-110
21.99.1476	7	+/-140
21.99.1477	10	+/-200
21.99.1478	15	+/-310
21.99.1479	20	+/-400

Marking: E213738 CM (UL) C(UL) UTP PATCH CORD 24AWG 4P ISO/IEC 11801 AND TIA/EIA 568 CAT6A

ELECTRONIC TEST:

- A. OPEN/SHORT : 100%.
- B. WORKING TEMPERATURES:-20~60°C
- C. Minimum Banding Radius: 46MM

Item No.	21.99.1470	21.99.1471	21.99.1472	21.99.1473	21.99.1475
	21.99.1476	21.99.1477	21.99.1478	21.99.1479	
REMARK: NO	CHA NO	DESC	VALUE UTP Cat. 6a Patch Cord, white		
DRAWN BY	WEIHAIYAN		<b>SECOMP</b>		
APPROVED BY	MORGAN				
DATE	2015.09.22				