




# 69001-981 CONNECTOR TYPE H, EN 60603, DIN 41612, FEMALE, 15 CONTACTS, PIN LENGTH 4.0 MM





4 × (5,08) = (71,12)





Requirement class 2 as per EN 60603 (DIN 41642)

Separate Coding

Coding on the connector

PRODUCT ATTRIBUTES
Product Type: Connector
Type: Female Connectors
Works With: Front Panels
Number of Contacts: 15
Contact Material: Silver Plated
Connector Pitch: 5.08 mm
Min Creepage Distance, Contact-Contact: 8 mm
Min Air Gap, Contact-Contact: 4.5 mm
Max Current @ 20°C: 6 A
Max Contact Resistance: 8 mO
Max Insertion and Withdrawal Force: 90 N
Test Voltage (Ueff), Contact-Contact: 1.55 kV
Test Voltage (Ueff), Contact-Earth: 2.5 kV
Row Assignment: Z; D

Male / Female DIN connector form H. Requirement class 2 as per EN 60603 (DIN 41642).

## **CERTIFICATIONS**



#### **North America**

All locations +1.763.422.2661 Chat with us: schroff.nvent.com

#### Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: schroff.nvent.com

nVent.com

### Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: schroff.nvent.com

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

#### Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: schroff.nvent.com



© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

nVent reserves the right to change specifications without notice.