

Brother HL-L6410DN 1200 x 1200 DPI A4 Wifi

Marque : Brother

Code produit: HLL6410DNRE1

Nom du produit : HL-L6410DN

Brother HL-L6410DN. Technologie d'impression: Laser. Nombre de cartouches d'impression: 1. Résolution maximale: 1200 x 1200 DPI. Taille de papier de série A ISO maximum: A4. Vitesse d'impression (noir, qualité normale, A4/US Letter): 50 ppm, Impression recto-verso. Wifi. Couleur du produit: Blanc



Vitesse d'impression		Connectivité	
Mode d'impression recto verso	Auto	Port USB *	✓
Couleur *	✗	Réseau	
Technologie d'impression *	Laser	Wifi *	✓
Impression recto-verso *	✓	Ethernet/LAN *	✓
Résolution maximale *	1200 x 1200 DPI	LAN Ethernet : taux de transfert des données	10,100,1000 Mbit/s
Vitesse d'impression (noir, qualité normale, A4/US Letter) *	50 ppm	Standards wifi	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Délai de copie de la première page (Noir, normal)	6,7 s	Paiement sans contact	✓
Caractéristiques		Algorithme de sécurité soutenu	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP
Couleurs d'impression *	Noir	représentation / réalisation	
Nombre de cartouches d'impression *	1	Mémoire interne *	1024 Mo
Langues de la description de page *	BR-Script 3, PCL 6, PDF 1.7	Design	
Capacité d'entrée et de sortie		position de marché *	Professionnel
Nombre total de bacs d'alimentation *	1	Couleur du produit *	Blanc
Capacité d'alimentation totale *	520 feuilles	Écran intégré *	✓
Capacité de sortie totale *	250 feuilles	Affichage couleur	✓
Bac multifonctions	✓	Type de commande	Tactile
Capacité d'entrée des plateaux à usages multiples	100 feuilles	Puissance	
Gestion du papier		Consommation électrique moyenne en mode Impression *	710 W
Taille de papier de série A ISO maximum *	A4	Consommation d'énergie (prêt)	430 W
Type de support du bac papier *	papier bond, Étiquettes, Papier recyclé, Papier épais, Papier fin	Consommation électrique (arrêt)	0,05 W
ISO, Format Series A (A0...A9) *	A4, A5, A6	Energy Star, consommation électrique typique (TEC)	0,62 kWh/semaine
Tailles du support d'impression non-ISO	Executive, Legal	Tension d'entrée AC	220 - 240 V
		Fréquence d'entrée AC	50/60 Hz
		Poids et dimensions	
		Largeur	402 mm
		Profondeur	396 mm

Poids et dimensions

Hauteur	319 mm
Poids	13,5 kg

Informations sur l'emballage

Poids du paquet	16 kg
-----------------	-------



4977766815154

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2024. Prints or copies of Information are only valid on the printed Publication date