

APC SRVL1KRILRK alimentation d'énergie non interruptible Double-conversion (en ligne) 1 kVA 900 W 6 sortie(s) CA

Marque : APC Code produit: SRVL1KRILRK

Nom du produit : SRVL1KRILRK







Features		Battery	
UPS topology * Output power capacity * Output power * Waveform *	poology * Double-conversion (Online) It power capacity * 1 kVA It power * 900 W Form * Sine Operation voltage (min) * 110 V Operation voltage (max) * 300 V Frequency * 40 - 70 Hz It operation voltage (max) 230 V It frequency 50/60 Hz It energy rating 945 J Incy 90% Factor 90% Factor 3:1 Indee Jency Power Off (EPO) Jency So dB Jency Bo dB Jency Power Off (EPO) Jevel 50 dB	Typical backup time at full load Typical backup time at half load Battery life (max) Battery recharge time	136 min 261 min 10 year(s) 8.5 h
Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (max) Output frequency Surge energy rating Efficiency Crest factor ECO mode Emergency Power Off (EPO) Noise level Audible alarm(s) Audible alarm modes		Pesign Form factor * Rack capacity Cooling type Built-in fan Product colour * Control type Display type LED indicators International Protection (IP) code Certification	Rackmount/Tower 4U Active Black Buttons LCD IP20 CB , CE, EAC, IEC 60204-2, IEC 60730-1, IEC 62040-1 safety, IEC 62619, KC, RCM, TISI, UKCA, UN 38.3, ROHS
Power source type Detachable power cord	AC	Operational conditions	30.3, 110113
Ports & interfaces AC outlet types Power plug	C13 coupler C14 coupler 6 AC outlet(s)	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Non-operating altitude	-20 - 50 °C 0 - 95% 0 - 95% 0 - 15000 m
AC outlets quantity USB port		Technical details	
USB port type Serial interface	USB Type-B ✓	Compliance certificates Weight & dimensions	CE, RoHS, UKCA
Serial interface type RS-232 ports	RS-232 1	Width Depth	438 mm 616 mm

Ports & interfaces		Weight & dimensions	
Modem (RJ-11) ports	1	Height	172 mm
Ethernet LAN (RJ-45) ports	1	Weight	36.3 kg
Emergency Power Off (EPO) connector	✓	Package width	800 mm
		Package depth	600 mm
Battery		Package height	480 mm
Battery technology Battery voltage	Lithium-lon (Li-lon) 48 V	Package weight	48.8 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	Output power cable, Phone (RJ-11), RJ-45, RS-232, USB cable





731304436782

0731304436782

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.