

APC SURT3000XLIX554 alimentation d'énergie non interruptible Double-conversion (en ligne) 3 kVA 2100 W 13 sortie(s) CA

Marque : APC Code produit: SURT3000XLIX554

Nom du produit : SURT3000XLIX554

APC SURT3000XLIX554. Topologie UPS: Double-conversion (en ligne), capacité de la puissance de sortie: 3 kVA, Puissance de sortie: 2100 W. Types de sortie AC: Coupleur C13, Coupleur C19, IEC Jumpers, Nombre de prises en sortie: 13 sortie(s) CA, Type d'interface série: RS-232. Technologie batterie: Sealed Lead Acid (VRLA), Temps de rechargement de la batterie: 2,5 h, Cartouche de batterie de rechange: APCRBC140. Format: Rack/Tour, Longueur de câble: 2,4 m, Certification: EN/IEC 62040-1-1, EN/IEC 62040-2, GOST, VDE. Largeur: 130 mm, Profondeur: 660 mm, Hauteur: 432 mm





Features		Battery	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max)	Double-conversion (Online) 3 kVA 2100 W Sine 160 V 280 V 40/70 Hz 220 V 240 V 50/60 Hz	Battery Hot-swap battery Automatic battery test Cold start Replacement battery cartridge Design Form factor * Cable length LED indicators	APCRBC140 Rackmount/Tower 2.4 m
Output frequency Surge energy rating Efficiency Crest factor	50/60 Hz 480 J 92% 3:1	Certification Operational conditions	EN/IEC 62040-1-1, EN/IEC 62040-2, GOST, VDE
Emergency Power Off (EPO) Output voltage Total Harmonic Distortion (THD)	3%	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95%
Noise level Surge protection Audible alarm(s)	55 dB	Operating altitude Non-operating altitude	0 - 3048 m 0 - 15240 m
Audible alarm modes Auto-restart	Alarm when on battery, Low battery alarm, Overload alarm	Technical details Compliance certificates Weight & dimensions	RoHS
Ports & interfaces		Width	130 mm
AC outlet types AC outlets quantity USB port Serial interface	C13 coupler, C19 coupler, IEC Jumpers 13 AC outlet(s)	Depth Height Weight Package width Package depth Package height	660 mm 432 mm 54.7 kg 603 mm 980 mm 347 mm

Ports & interfaces		Weight & dimensions	
Serial interface type	RS-232	Package weight	63.6 kg
SmartSlot	✓	Packaging data	
Battery		Cables included	RS-232
Battery technology	Sealed Lead Acid (VRLA)	Manual	✓
Battery recharge time	2.5 h	Logistics data	
		Harmonized System (HS) code	85078000





731304268895

0731304268895

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.