



## Eaton EVMAF132A unité de distribution d'énergie 24 sortie(s) CA 39U Noir

Marque : Eaton

Code produit: EVMAF132A

Nom du produit : EVMAF132A

Eaton EVMAF132A. Types de PDU: Géré, Capacité du rack: 39U, Type: Monophasé. Nombre de prises en sortie: 24 sortie(s) CA, Types de sortie AC: Coupleur C13, C39 coupler, Prise mâle: IEC 60309. Longueur de câble: 3 m, Algorithme de sécurité soutenu: SNMP. Protocoles réseau pris en charge: HTTPS. Tension nominale à l'entrée: 200-240 V, Intensité (max.): 32 A, Fréquence d'entrée AC: 50/60 Hz



| Design                              |                           | Caractéristiques                   |           |
|-------------------------------------|---------------------------|------------------------------------|-----------|
| Types de PDU *                      | Géré                      | Sorties codées par couleur         | ✓         |
| Type                                | Monophasé                 | Longueur de câble                  | 3 m       |
| Capacité du rack *                  | 39U                       | Algorithme de sécurité soutenu     | SNMP      |
| Montage                             | verticale                 | <b>Caractéristiques de gestion</b> |           |
| Matériau du boîtier/corps           | Aluminium                 | Protocoles réseau pris en charge   | HTTPS     |
| Couleur du produit                  | Noir                      | <b>Puissance</b>                   |           |
| Écran                               | LCD                       | Tension nominale à l'entrée *      | 200-240 V |
| <b>Connectivité</b>                 |                           | Fréquence d'entrée AC              | 50/60 Hz  |
| Nombre de prises en sortie *        | 24 sortie(s) CA           | Intensité (max.) *                 | 32 A      |
| Prise mâle                          | IEC 60309                 | Puissance max.                     | 7400 W    |
| Types de sortie AC *                | Coupleur C13, C39 coupler | <b>Poids et dimensions</b>         |           |
| Nombre de port ethernet LAN (RJ-45) | 4                         | Largeur                            | 52 mm     |
| Nombre de ports USB                 | 2                         | Profondeur                         | 53 mm     |
|                                     |                           | Hauteur                            | 1730 mm   |



3553340696961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-JAN-2024. Prints or copies of Information are only valid on the printed Publication date